

BWBZ Plate Feeding Machine



BW/BZ Plate Feeding Machine

BW Plate Feeding Machine

Model	Width of plate (mm)	Distance between head and tail gear spindle (mm)	Velocity (mm)	Feeding granularity (mm)	Capacity (t/h)	Motor power (kw)	Dimensions L×W×H(mm)	weight (kg)
BW250-11.5								
BW240-10	2400	10000	0.018-0.055	≤ 1500	220-680	45	12650 × 4695×3350	83400
BW220-10	2200	10000	0.018-0.055	≤ 1500	220-680	45	12650 × 4495×3350	80400
BW180-12	1800	12000	0.05	≤ 800	360	45	14723 × 6697×2080	67806
BW180-8	1800	8000	0.022-0.046	≤ 800	100-1000	37	10300 × 4295×3650	53025
BW160-9	1600	9000	0.076	≤ 800	180	22	11250 × 5716×2240	34763
BW160-6	1600	6000	0.017-0.17	≤ 800	61-610	22	8354 × 6099×2100	25032
BW150-15	1500	15000	0.006-0.06	≤ 700	20-200	22	17350 × 5595×1705	58800
BW150-10.5	1500	10500	0.006-0.06	≤ 700	20-200	22	12850 × 5595×1705	49415
BW150-5	1500	5000	0.014-0.08	≤ 700	85-288	15	7620 × 5440×1950	18718
BW140-18.03	1400	18030	0.006-0.06	≤ 900	20-200	22	20380 × 6440×2030	50980
BW140-16	1400	16000	0.006-0.06	≤ 900	20-200	22	18310 × 6447×2030	45999

BW140-8	1400	8000	0.017-0.17	≤ 900	100-200	22	10350 × 5948×1840	29298
BW125-12	1250	12000	0.014-0.08		45-150	18.5	14600 × 5460×2000	31898
BW125-6	1250	6000	0.014-0.08		45-150	11	8620 × 5240×1950	18930
BWZ125-4.5	1200	4500	0.054		150	15	7183 ×3616×2071	30500
BW120-19	1200	19000	0.014-0.09	≤ 600	45-150	22	21620 × 5460×2000	41058
BW120-11	1200	11000	0.01-0.1	≤ 600	50-100	15	11463 × 5029×2860	23535
BW120-6	1200	6000	0.01-0.1	≤ 600	80-160	11	8620 × 5160×1600	15660
BW120-4	1200	4000	0.014-0.08	≤ 600	45-150	11	5810 × 5160×1480	12660
BW100-12	1000	12000	0.05-0.1	≤ 500	60-130	15	1350 0× 4215×1675	23525
BW100-6	1000	6000	0.01-0.1	≤ 500	80-160	11	8620× 4960×1600	15560

BW chain plate feeder is a kind of bulk material transmission equipment, which transfers intermittent feeding to continuous feeding. Our newly BW plate feeder which is developed on the basis of foreign advanced technology has advantages of huge traction, little material leakage, stable operation, longevity and easy to maintenance.

BZ Plate Feeding Machine:

BZ250-11.5	2500	11460	0.01-0.07	≤1800	550-900	2x45	12000×5053×2890	105000
BZ240-10	2400	10000	0.02-0.06	≤1600	≤ 850	2x37	12000×4953×2890	95000
BZ230-10	2300	10000	0.01-0.07	≤1500	≤ 800	45	12000×4853×2890	86000
BZ220-10	1800	10000	0.01-0.07	≤ 1200	≤ 700	45	12000×4753×2890	85000
BZ200-9.8	2000	9800	0.01-0.07	≤ 1000	≤ 500	37	12000×4553×2890	82000
BZ180-10	1800	10000	0.01-0.07	≤ 1000	≤ 500	37	12200×4553×2890	66000
BZ180-9.8	1800	9800	0.01-0.07	≤ 1000	≤ 500	37	12000×4553×2890	63000
BZ180-9	1800	9000	0.01-0.07	≤ 1000	≤ 500	37	11250×4553×2890	63000
BZ180-8.75	1800	8750	0.01-0.07	≤1000	≤ 500	37	11050×4553×2890	61000
BZ180-8	1600	8000	0.01-0.07	≤1000	≤ 500	37	10250 ×4153×2890	59000
BZ160-9	1600	9000	0.01-0.07		27-270	30	11250 ×4153×2890	50000

Note: weight in this table is not including motor weight.