

PC series Hammer Crusher



[PC series Hammer Crusher](#)

Model	Rotor diameter/length mm	Rotor speed r/min	Feeding size mm	Max. material size	Discharging granularity mm	Capacity t/h	Power of motor kw	Weight (T)	Dimensions mm
PC-1618	φ1600/1800	590	1200×1740	350	20	220-280	500	32.4	6256×3620×2700
PC-1414	φ1400/1400	750	1050×1540	250	20	120-170	280	17.2	2790×2800×2310
PC-1212	φ1250/1250	750	650×1330	200	20	90-110	185	19.1	4475×3162×2250
PC-1010	φ1000/1000	1000	580×1060	200	8	25-35	185	7.59	3514×2230×1518
PC-1010	φ1000/1000	1000	580×1060	200	10	30-50	160	7.59	3514×2230×1518
PC-1010	φ1000/1000	1000	580×1060	200	15	40-60	132	7.59	3514×2230×1516
PC-108	φ1000/800	1000	580×850	200	13	25-40	110	6.5	3206×2210×1515
PC-88	φ800/800	1000	350×850	200	15	35-45	55	3.05	1515×2831×1040
PC-86	φ800/600	1000	350×570	200	10	20-25	55	2.45	1515×2586×1040
PC-66	φ600/600	1000	295×570	100	10	12~18	45	2.14	1315×840×1501
PC-64	φ600/400	1000	295×450	100	15	10~12	18.5	1.03	1054×972×1117
PC-44	φ400/400	1500	145×450	100	10	5~8	7.5	0.9	744×942×878
PC-41	φ400/175	1000	145×270	50	3	0.5	5.5	0.5	812×1056×1315

Main usage:

PC series hammer crusher suits to crush some brittle materials, such as coal,

salt, plaster, alum, brick, tile, limestone, etc, of which compression strength is not more than 100MPa, and temperature is not higher than 15%.