

## PYB\PYZ\PYD series Spring Cone Crusher



[PYB\PYZ\PYD series Spring Cone Crusher](#)

Model	Max. feeding size ( mm )	Discharging opening width ( mm )	Capacity ( T / H )	Power (KW )	Weight(T) ( not including motor )
PYD2200	100	5~15	120-340	280 -260	75.3
PYZ2200	230	10~30	200-580	280 -260	74.6
PYB2200	300	30-60	59-1000	280 -260	75
PYD1750	85	5~13	75-230	160	50.2
PYZ1750	185	10~30	115-320	160	50.3
PYB1750	215	25-50	280-480	160	50.3
PYD1200	50	3~15	18-105	110	25.3
PYZ1200	100	8~25	42-135	110	25
PYB2200	300	30-60	590-1000		
PYB1200	145	20-50	110-168	110	24.7
PYD900	50	3~13	15-50	55	11.3
PYZ900	60	5~20	20-65	55	11.2
PYB900	115	15-50	50-90	55	11.2
PYD600	35	3~13	12~23	30	5.5
PYB600	65	12~25	40	30	5

**Main purpose:**

this crusher series is best suited to crush medium to hard iron ore and rock.

Ore crushing chamber depends on the type, standard applied for medium crushing; and the short head one for fine crushing.