

YK/YZ series Round Vibrating Screen



YK/YZ series Round Vibrating Screen

Main technical parameter of YZ type round vibrating screen :								
Model	Layers of screen mesh	Area of screen mesh (m ²)	Size of screen hole (mm)	Max. feeding granularity (mm)	Capacity (m ³ /h)	Motor power (KW)	Weight (Kg) (excluding motor)	Angle
3YZ-1860								
3YZ-1848	3	8.64	5-100	400	56-330	15	6935	20°
3YZ-1548	3	7	5-50	400	50-275	15	6070	20°
3YZ-1542	3	6	5-50	200	50-208	15	5961	20°
3YZ-1236	3	4	5-50	200	9-93	11	4290	20°
3YZ-1230	3	3.6	5-50	200	8-80	7.5	3050	20°
2YZ-1860	3	10.8	5-100	400	70-650	15	7700	20°
2YZ-1848	2	8.64	5-100	400	56-330	15	7740	20°
2YZ-1542	2	6	5-50	400	50-208	15	5536	20°
2YZ-1230	2	3.6	5-50	200	8-80	7.5	2700	20°
2YZ-1020	2	2	3-50	100	8-50	5.5	1490	15°
2YZ-930	2	2.7	3-50	100	8-70	5.5	1680	20°
2YZ-924	2	2.16	3-50	100	7-60	5.5	2057	20°
YZ-1848	1	8.64	5-100	400	56-330	15	7122	20°
YZ-1230	1	3.6	5-50	200	8-80	5.5	1750	20°

YZ-1020	1	2	3-50	100	8-50	5.5	1400	20°
YZ-918	1	1.62	3-50	100	5-50	5.5	1299	20°

Main technical parameter of YK type round vibrating screen								
Model	Layers of screen mesh	Area of screen mesh (m ²)	Size of screen hole (mm)	Max. feeding granularity (mm)	Capacity (m ³ /h)	Motor power (KW)	Weight (Kg) (excluding motor)	Angle
3YK-2460	3			200	450-650	37	762	20°
3YK-2160	3	12.6	5-100	450	66-720	30	12757	20°
3YK-2154	3	11.3	5-100	400	73-683	22	9857	20°
3YK-1854	3	9.72	5-100	400	32-360	22	8640	15°
3YK-1848	3	8.8	5-100	400	56-330	22	6935	20°
3YK-1548	3	7.2	5-50	400	47-275	15	6070	20°
3YK-1545	3	6.75	5-50	400	44-258	15	5832	15°
3YK-1535	3	5.25	5-50	400	20-125	15	5710	20°
3YK-1245	3	5.4	5-50	200	32-200	11	4460	15°
2YK-2460	2	14.4	5-150	200	450-650	30	8013	20°
2YK-2280	2	17.6	5-150	200	550-700	30	10180	20°
2YK-2160	2	12.6	5-100	200	370-500	30	7833	20
2YK-2154	2	11.3	5-100	200	400-600	22	7851	20°
2YK-1854	2	9.72	5-100	400	63-586	22	7602	20°
2YK-1848	2	8.8	5-100	400	56-330	15	7710	20°
2YK-1545	2	6.75	5-50	400	44-258	15	5090	20°
2YK-1245	2	5.4	5-50	200	35-206	11	4320	15°
YK-2460	1	14.4	5-150	400	150-810	8	6200	20°
YK-2154	1	11.3	5-100	400	73-683	22	5269	20°
YK-1854	1	200	63-586	18.5	5102	18.5	5102	20°
YK-1848	1	8.8	5-100	400	56-330	11	7122	20°
YK-1545	1	6.75	5-50	400	22-150	11	3900	20°
YK-1535	1	5.25	5-50	200	34-200	11	3355	15°

Main applications:

this Round Vibrating Screen is specially designed for screening of stone quarries, also for products grading in coal preparation, mineral processing, building materials, electrical and chemical industries, etc.