

Screening Equipment>>ZS series Horizontal Vibrating Screen



ZS series Horizontal Vibrating Screen

Horizontal Vibrating Screen:

Model	Layers of screen mesh	Area of screen mesh (m ²)	Size of screen hole (mm)	Max. feeding granularity (mm)	Capacity (m ³ /h)	Motor power (KW)	Weight (Kg) (excluding motor)
3ZS-2160	3	11.3	5-80	300	41-375	2x22	13400
2ZS-2160	2	11.3	5-80	300	41-375	2x18.5	10500
ZS-2160	1	11.3	5-80	300	41-375	2x18.5	8870
2ZS-2154	2	10.2	5-80	300	34-344	15x2	8000
ZS-2148	1	9	5-80	300	31-313	11x2	6500
3ZS-1854	3	8.7	5-80	300	31-306	30	6500
2ZS-1854	2	8.7	5-80	300	31-306	30	6300
2ZS-1848	2	7.7	5-80	300	25-275	37	8800
2ZS-1842	2	6.8	5-80	300	25-241	7.5x2	6800
ZS-1836	1	5.8	5-30	300	21-100	5.5x2	5700
3ZS-1542	3	5.6	3-50	300	13-138	11x2	6922
2ZS-1530	2	4.7	5-30	300	17-84	5.5x2	5600

ZS-1530	1	4	5~30	300	14-69	4x2	5000
2ZS-1236	2	3.9	5~30	200	13-63	4x2	4000
ZS-1224	1	2.6	5~30	200	9-44	4x2	3000

Main applications:

this horizontal Vibrating Screen is specially designed for screening of stone quarries, also for grading of products in coal preparation, mineral processing, building materials, electrical and chemical industries, etc.